TECHNICAL DATA SHEET · NATURAL STONE

# S10

Document **TDS-S10**
Issued **27 October 2026**
Products **1**

Covers S10 Flamed.



S10 Flamed

| PRODUCT | |
|---|---|
| Finish | Flamed |
| Colour | Charcoal & Black |

| SIZE AND UNITS | |
|---|---|
| Work size, L × W × H, mm | 380 × 100 × 50 |
| Units per m², 10 mm joint | 42.7 |
| Weight per unit, kg | – |
| Units per pallet | – |
| Area per pallet, m² | – |
| Weight per pallet, kg | – |

PERFORMANCE Testing in progress. No result is stated until a laboratory report is issued.

| | |
|---|---|
| Durability class | – |
| Compressive strength f'uc, MPa | – |
| Initial rate of absorption, kg/m²/min | – |
| Cold water absorption, % | – |
| Efflorescence | – |
| Fire resistance level | – |

| TEST EVIDENCE | |
|---|---|
| Laboratory | – |
| Report | – |
| Date | – |

Sizes are nominal averages. Clay and natural stone vary in colour, texture and size between units and between batches; allow for it in setting out.

Images are indicative. Blend from at least three to four packs as you lay. View a physical sample or visit the showroom at 73–81 North Street, Richmond VIC 3121 before ordering.

Values marked — are not yet available. This sheet is reissued, with a new issue date, when they are.