TECHNICAL DATA SHEET · NATURAL STONE

S25

Document **TDS-S25**
Issued **27 October 2026**
Products **2**

Covers S25 Sandblasted, S25 Split.



S25 Sandblasted



S25 Split

PRODUCT		
Finish	Sandblasted	Split
Colour	Sand & Gold	Sand & Gold
SIZE AND UNITS		
Work size, L × W × H, mm	380 × 100 × 50	380 × 100 × 50
Units per m², 10 mm joint	42.7	42.7
Weight per unit, kg	–	–
Units per pallet	–	–
Area per pallet, m²	–	–
Weight per pallet, kg	–	–
PERFORMANCE Testing in progress. No result is stated until a laboratory report is issued.		
Durability class	–	–
Compressive strength f'uc, MPa	–	–
Initial rate of absorption, kg/m²/min	–	–
Cold water absorption, %	–	–
Efflorescence	–	–
Fire resistance level	–	–
TEST EVIDENCE		
Laboratory	–	–
Report	–	–
Date	–	–

Sizes are nominal averages. Clay and natural stone vary in colour, texture and size between units and between batches; allow for it in setting out.

Images are indicative. Blend from at least three to four packs as you lay. View a physical sample or visit the showroom at 73–81 North Street, Richmond VIC 3121 before ordering.

Values marked — are not yet available. This sheet is reissued, with a new issue date, when they are.